This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.


ASSY QTY B/O


Part #


SWA10A-700

|     | REVISIONS |  |            |         |          |  |  |  |
|-----|-----------|--|------------|---------|----------|--|--|--|
| REV | ECR       | DESCRIPTION                                | DATE       | INITIAL | APPROVED |  |  |  |
| 3   |           | AS DRAWN BY CANAM                          | 11/13/2012 | JAG     |          |  |  |  |
| 4   | 16-0271   | CH'D DIM WAS 2X R.05 IS 2X R BLEND CORNER. | 12/28/2016 | RJC     | JAG      |  |  |  |

## SEE ATTACHED DEVIATION








Description

1 WIRE CLAMP

Material

6061-T6



**B/O INFORMATION OR SPECIFICATIONS** 

| N A-A                    |                    |              |     |  |                          |     |  |  |  |
|--------------------------|--------------------|--------------|-----|--|--------------------------|-----|--|--|--|
|                          | DART               |              |     |  |                          |     |  |  |  |
| TITLE                    |                    |              |     |  |                          |     |  |  |  |
| DWG NO.                  | DWG NO. SWA10A-700 |              |     |  |                          |     |  |  |  |
| HEAT<br>TREAT            | HEAT               |              |     | UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX + .01 ANGLES ± .5° .X ± .1 SURFACES = 125/ |                          |     |  |  |  |
| SPEC MIL-A-<br>DRAWN BY: | 8625, TYPE         | III OLACO II |     |  | L SHARP EDGES            | 7   |  |  |  |
| CHECKED:<br>OPPS APPR:   | MACKOV             |              |     | AFTER PLA<br>3. INTERPRE   | T DIM AND TOL PER        |     |  |  |  |
| QA APPR:                 | ANDERS<br>LINDSAY  |              |     | ASME Y14.  | 5M-2009<br>USED ON MODEL |     |  |  |  |
| APPROVED:<br>SCALE       | GILBERT            | DATE         | 1/2 | 22/2002  | SHEET 1 OF               | : 1 |  |  |  |
|                          | 1.1                |              | 1/2 | 2/2002   | 3HEET TOP I              |     |  |  |  |

| Entered: Date:   |                                       |   | OADT                   |  |  |  |
|--|---------------------------------------|---|------------------------|--|--|--|
|  | WORK ORDER NON-CONI                   | FORMANCE / ROUTE UPDATE   | DAR                    |  |  |  |
| NCR No.  |                                       | Route update only   |                        |  |  |  |
| Job:   | DISPOSITION                           | DEPARTMENT/PROCESS  |                        |  |  |  |
| -  | Rework                                | Skid-tube Cross tube Eng. (Non-A  | W) X Engineering       |  |  |  |
| Part No. SWA10A-700 REV. 4   | Scrap                                 | Machining Small Fab Prod. Eng. Co   |                        |  |  |  |
|  | Use-as-is                             | Large Fab Finishing Rec/Store/Packagi                                     | ing Supplier           |  |  |  |
|  |                                       |   | Quality                |  |  |  |
| Date :   | Sequence #:                           | QTY Affected :  | MRB (QSI042)           |  |  |  |
| Description V  | Vork Order Deviation                  | Disposition   | JAN 23, 2019           |  |  |  |
|  |                                       | •   | Completed By           |  |  |  |
| When assembling a SWA10A-3 it w                                    | as noticed that the clamping          |   | Completed by           |  |  |  |
| compression of the SWA10A-700 o                                    | onto the 3 conductor is not adequate. | This deviation is acceptable.   |                        |  |  |  |
| A modified / custom SWA10A-700 was used in place of the standard S | with a clamping thickness of 0.175"   | The clamping force has been visually verified by A. Patry & M. Lee. 3 MBB | Lead hand / Supervisor |  |  |  |
|  |                                       |   |                        |  |  |  |
|  |                                       | The fit, form, and function of the part will be as originally intended.   |                        |  |  |  |
|  |                                       |   | QC / QA Coordinator    |  |  |  |
|  |                                       |   |                        |  |  |  |
|  |                                       |   |                        |  |  |  |
| PER MBB  |                                       |   |                        |  |  |  |
| Root Cause   |                                       | FAULT CATEGORY  |                        |  |  |  |
|  | Pressure/Forced                       | Contamination Power Loss/Surge  | Positioned Wrong       |  |  |  |
| Operator   | Bending                               | Misaligned/off center Folio/Program                                       | Outside Tolerance      |  |  |  |
| Manufacturing Process  | Crushing                              | BOM/Route Grain Direction   | Drawing                |  |  |  |
| Equip/Tooling Handling/Presservation                               | Cracks                                | Broken/Damage/Defect Weld   | Finish                 |  |  |  |
| Material   | Crimp/Kink/Ripple/Wave/Twist          | Incomplete/Unclear Instructions Wrong Stock Pulled                        | Part Lost/Missing      |  |  |  |
| Product Improvement X  | Marks/Chatter                         | Drill Holes Out of Sequence   | Misread                |  |  |  |
| Process Improvement  | Mislabeled                            | Fit/Function Off-set/Set-up   |                        |  |  |  |
|  | Other/Details:                        |   |                        |  |  |  |
| Human Factors  |                                       |   |                        |  |  |  |
|  |                                       |   | 1)                     |  |  |  |
|  |                                       |   |                        |  |  |  |
|  |                                       |   |                        |  |  |  |